


SHREENATHJI & CO.

SEALS FOR HYDRAULICS & PNEUMATICS

ROD SEAL

PNRS010



Features:

Piston seal PNPS007 is a U cup type piston seal made of highly abrasion resistant polyurethane having very thin outer contact lip suitable for low pressure pneumatic application.

Composition:

Material:	Polyurethane
Code	PUAB92

Properties:

- 1 Low friction due to thin outer lip
- 1 High resistance to abrasion
- 1 Easy installation

Application:

- Ø Pneumatics tools & equipments

General Technical Data:

Temperature range	-20°C to +100°C
Working Pressure	Up to 12 bar
Surface Speed	1 m/s.

Surface finish:

Roughness depth	R(max.)	R p/Rz	tp
Sliding surface	£4 µm	<0,5	(25% R _{max}) = 50 % - 75 %
Bottom of groove	£10 µm	< 0.5	


Fitting:

PNRS-010 is very easy to fit. Careful fitting of the seal is a prerequisite for its perfect functioning.

We have given all metric(mm) sizes here. For Imperial (inch) sizes please contact SHREENATHJI at info@shreenathjiandco.com

SHREENATHJI & CO.

SEALS FOR HYDRAULICS & PNEUMATICS



OUR STANDARD SIZE LIST

[illegible]